

F Top Diameter

Continental Series

Rope Halyard Ground Set Installation

ESR - External Single Revolving

Truck and Ornament (Options Available)

See Specification Box Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Solid Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **D** Butt Diameter **ESR-GS** Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		

Lightning Spike -

3/4" Diameter Steel Rod

soil conditions.

ESR30D51

SAT



TRK-9610

In-Line Truck Single Revolving



CLA-9090-SAT | 7.5' from bottom Cleat Only



BAL-0512-GLD-**HD Gold Anodized** Aluminum Ball



COL1-A05S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .188"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 120 lbs.	
Hardware Weight: 9 lbs.	
Ground Sleeve Weight: 29 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 94 mph	
* Max Wind Speed No Flag: 131 mph	
* Wind Speed Specifications from	