

**F** Top Diameter

## **Continental Series**

Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

## ESR - External Single Revolving

See Specification Box

## Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Solid Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **D** Butt Diameter **ESR-GS** Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site Lightning Spike soil conditions.

| Customer Name: |           |        |
|----------------|-----------|--------|
| Dealer:        |           | Qty: 1 |
| Project:       | Location: |        |
| Notes:         |           |        |
|                |           |        |
|                |           |        |
|                |           |        |
|                |           |        |

3/4" Diameter Steel Rod

**ESR35C61** 

SAT



TRK-9610

In-Line Truck Single Revolving



CLA-9090-SAT | 8' from bottom Cleat Only



BAL-0612-GLD-ES **HD Gold Anodized** Aluminum Ball



COL1-A06S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

| Specifications                        |  |  |
|---------------------------------------|--|--|
| A. Mounting Height: 35'               |  |  |
| B. Set Depth: 3'-6"                   |  |  |
| C. Total Length: 38'-6"               |  |  |
| D. Butt Diameter: 6"                  |  |  |
| E. Wall Thickness: .156"              |  |  |
| F. Top Diameter: 3.5"                 |  |  |
| Flagpole Sections: 1                  |  |  |
| Shaft Weight: 162 lbs.                |  |  |
| Hardware Weight: 10 lbs.              |  |  |
| Ground Sleeve Weight: 39 lbs.         |  |  |
| * Max Flag Size: 6' x 10'             |  |  |
| * Max Wind Speed w/Nylon Flag: 87 mph |  |  |
| * Max Wind Speed No Flag: 116 mph     |  |  |
| * Wind Speed Specifications from      |  |  |