

Continental Series

ESR - External Single Revolving Rope Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Solid Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **D** Butt Diameter **ESR-GS** Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Lightning Spike -

3/4" Diameter Steel Rod

ESR40C81

SAT



TRK-9610

In-Line Truck Single Revolving



CLA-9090-SAT | 8.5' from bottom Cleat Only



BAL-0812-GLD-ES **HD Gold Anodized** Aluminum Ball



COL1-A08S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 40'
B. Set Depth: 4'-0"
C. Total Length: 44'-0"
D. Butt Diameter: 8"
E. Wall Thickness: .156"
F. Top Diameter: 4"
Flagpole Sections: 1
Shaft Weight: 239 lbs.
Hardware Weight: 12 lbs.
Ground Sleeve Weight: 55 lbs.
* Max Flag Size: 8' x 12'
* Max Wind Speed w/Nylon Flag: 107 mph
* Max Wind Speed No Flag: 157 mph
* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

soil conditions.