

## **Continental Series**

ESR - External Single Revolving Rope Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Heavy-Duty Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube ESR-GS-1012 Cleat (Security Options Available) See Specification Box **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box

Customer Name:

Dealer: Qty: 1

Project: Location:

Notes:

Perimeter caulked by Installer

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

ESR55D13G-TAY-O0F-SK-C2C-FSA

CAFP\_010819\_1pg

Set

6"

12

**ESR55D13** 

- SAT



**TRK-9420-58**HD Truck - Single Rev.
Sealed Bearings



HD Gold Anodized

Aluminum Ball



CLA-9090-SAT | 10' from bottom Cleat Only



COL1-A10S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 55'
B. Set Depth: 5'-6"
C. Total Length: 60'-6"
D. Butt Diameter: 10"
E. Wall Thickness: .188"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 450 lbs.
Hardware Weight: 25 lbs.
Ground Sleeve Weight: 87 lbs.
* Max Flag Size: 10' x 15'
* Max Wind Speed w/Nylon Flag: 102 mph
* Max Wind Speed No Flag: 139 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

- 1 -

AY-OUF-SK-C2C-FSA

Note: Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified

Engineer familiar with site