

## **Continental Series**

ESR - External Single Revolving Rope Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Heavy-Duty Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube

ESR-GS-1012



## **D** Butt Diameter

Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate Lightning Spike -

3/4" Diameter Steel Rod

Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

**Customer Name:** Dealer: Qty: 1 Project: Location: Notes:

**ESR60D13** 





TRK-9420-58 HD Truck - Single Rev. Sealed Bearings



CLA-9090-SAT | 10.5' from bottom Cleat Only



**BAL-1058-GLD HD Gold Anodized** 

Aluminum Ball



COL1-A10S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 60'
B. Set Depth: 6'-0"
C. Total Length: 66'-0"
D. Butt Diameter: 10"
E. Wall Thickness: .188"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 503 lbs.
Hardware Weight: 27 lbs.
Ground Sleeve Weight: 90 lbs.
* Max Flag Size: 12' x 18'
* Max Wind Speed w/Nylon Flag: 86 mph
* Max Wind Speed No Flag: 118 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

| ANSI/NAAMM FP 1001-07

Set

6"