

Continental Series

Rope Halyard Ground Set Installation

ESR - External Single Revolving

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Heavy-Duty Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube ESR-GS-1012 Cleat (Security Options Available) See Specification Box **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

-

ESR80H23

SAT



TRK-9420-58 HD Truck - Single Rev. Sealed Bearings



CLA-9090-SAT | 12.5' from bottom Cleat Only



BAL-1258-GLD HD Gold Anodized Aluminum Ball



FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 80'
B. Set Depth: 8'-0"
C. Total Length: 88'-0"
D. Butt Diameter: 12"
E. Wall Thickness: .375"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 1130 lbs.
Hardware Weight: 30 lbs.
Ground Sleeve Weight: 119 lbs.
* Max Flag Size: 15' x 25'
* Max Wind Speed w/Nylon Flag: 107 mph
* Max Wind Speed No Flag: 144 mph
* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

ESR80H23G-TAY-O0G-SK-C2N-FSA CAFP_010819_1pg