

Monarch Series

ICC - Internal Cam Cleat Rope Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Continuous Piano Hinge, and Manually Operated Cam Cleat **D** Butt Diameter **ICC-GS**

Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer)

3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod

Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ICC20B51G-T0Y-O2M-C0L-FSA

4' - 6"

B Depth

Set

ICC20B51



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

ES HD Gold Anodized

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ICC - CAM CLEAT Flush Mount Hinged Door

Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .125"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 72 lbs.	
Hardware Weight: 17 lbs.	
Ground Sleeve Weight: 23 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 117 mph	
* Max Wind Speed No Flag: 204 mph	
* Wind Speed Specifications from	

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -