

Monarch Series

ICC - Internal Cam Cleat Rope Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Continuous Piano Hinge, and Manually Operated Cam Cleat **D** Butt Diameter **ICC-GS** 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified 3/16" Steel Support Plate Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ICC35C62G-T0Y-O2N-C0W-FSA

ICC35C62



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-**ES**

HD Gold Anodized Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ICC - CAM CLEAT Flush Mount Hinged Door

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 6"	
E. Wall Thickness: .156"	
F. Top Diameter: 3.5"	
Flagpole Sections: 2	
Shaft Weight: 169 lbs.	
Hardware Weight: 18 lbs.	
Ground Sleeve Weight: 39 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 74 mph	
* Max Wind Speed No Flag: 93 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -