

Monarch Series

Rope Halyard Ground Set Installation

ICC - Internal Cam Cleat

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Continuous Piano Hinge, and Manually Operated Cam Cleat **D** Butt Diameter **ICC-GS** 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified 3/16" Steel Support Plate Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Qty: 1
Location:

ICC40C82G-T0Y-O2P-C1S-FSA

ICC40C82



TRK-9660

Int. Revolving Truck Sealed Bearings




SAT

BAL-0812-GLD-**ES HD Gold Anodized**

Aluminum Ball



COL1-A08S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ICC - CAM CLEAT Flush Mount Hinged Door

Charifications
Specifications
A. Mounting Height: 40'
B. Set Depth: 4'-0"
C. Total Length: 44'-0"
D. Butt Diameter: 8"
E. Wall Thickness: .156"
F. Top Diameter: 3.5"
Flagpole Sections: 2
Shaft Weight: 250 lbs.
Hardware Weight: 22 lbs.
Ground Sleeve Weight: 55 lbs.
* Max Flag Size: 8' x 12'
* Max Wind Speed w/Nylon Flag: 94 mph
* Max Wind Speed No Flag: 140 mph
* Wind Speed Specifications from
ANCUALA ANALED 4004 07

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -