

Sentry II Series

IRC - Internal Cam Cleat Rope Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Flush Access Door with Keyed Lock, Reinforced Door Frame, and Manually Operated Cam Cleat **IRC-GS D** Butt Diameter 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation dimensions should be 3/16" Steel Plate Welded to Sleeve 9 determined by a qualified 3/16" Steel Support Plate Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRC20D61G-T0Y-O2N-C0W-FSA

IRC20D61



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-**ES**

HD Gold Anodized Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRC - CAM CLEAT Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 6"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 118 lbs.	
Hardware Weight: 20 lbs.	
Ground Sleeve Weight: 28 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 229 mph	
* Max Wind Speed No Flag: 328 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -