


Sentry II Series

IRC - Internal Cam Cleat Rope Halyard **Ground Set Installation**



Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRC30D62G-T0Y-O2N-C0W-FSA

IRC30D62



TRK-9660

Int. Revolving Truck Sealed Bearings



ES **HD Gold Anodized**

Aluminum Ball

SAT



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRC - CAM CLEAT Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 6"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 2	
Shaft Weight: 162 lbs.	
Hardware Weight: 18 lbs.	
Ground Sleeve Weight: 36 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 122 mph	
* Max Wind Speed No Flag: 197 mph	
* Wind Speed Specifications from	

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -