

Independence Series

IRW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **IRW-GS D** Butt Diameter 9 <u>4</u> Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve .9 dimensions should be 3/16" Steel Support Plate determined by a qualified 12" Engineer familiar with site Lightning Spike soil conditions.

| Customer Name: | | |
|----------------|-----------|--------|
| Dealer: | | Qty: 1 |
| Project: | Location: | |
| Notes: | | |
| | | |
| | | |
| | | |
| | | |
| | | |

3/4" Diameter Steel Rod

IRW20D61G-T0Y-O2N-C0W-FSA

IRW20D61



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH
Reinforced Welded
Door Frame

| Specifications | | |
|----------------------------------------|--|--|
| A. Mounting Height: 20' | | |
| B. Set Depth: 2'-0" | | |
| C. Total Length: 22'-0" | | |
| D. Butt Diameter: 6" | | |
| E. Wall Thickness: .188" | | |
| F. Top Diameter: 3.5" | | |
| Flagpole Sections: 1 | | |
| Shaft Weight: 119 lbs. | | |
| Hardware Weight: 20 lbs. | | |
| Ground Sleeve Weight: 28 lbs. | | |
| * Max Flag Size: 4' x 6' | | |
| * Max Wind Speed w/Nylon Flag: 229 mph | | |
| * Max Wind Speed No Flag: 328 mph | | |
| | | |
| * Wind Speed Specifications from | | |
| ANSI/NAAMM FP 1001-07 | | |

CAFP_010819_1pg -1-