

## **Independence Series**

IRW - Internal with Winch Wire Halyard Ground Set Installation

## Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube

Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle

## **D** Butt Diameter

Aluminum Collar (Options Available)

See Specification Box
Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod **Note:** Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

**IRW-GS** 

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRW30D61G-T0Y-O2N-C0W-FSA

9

4

**B** Depth

Set

...

12"

## **IRW30D61**



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



IRW - WINCH
Reinforced Welded
Door Frame

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 6"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 168 lbs.	
Hardware Weight: 22 lbs.	
Ground Sleeve Weight: 36 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 122 mph	
* Max Wind Speed No Flag: 197 mph	
* Wind Speed Specifications from	

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg -1-