

Independence Series

IRW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube

Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle

D Butt Diameter

Aluminum Collar (Options Available)

See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

Lightning Spike -3/4" Diameter Steel Rod Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

IRW-GS

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRW35C61G-T0Y-O2N-C0W-FSA

9

<u>4</u>

B Depth

Set

..9

12"

IRW35C61



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES **HD Gold Anodized**

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 6"	
E. Wall Thickness: .156"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 167 lbs.	
Hardware Weight: 23 lbs.	
Ground Sleeve Weight: 39 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 87 mph	
* Max Wind Speed No Flag: 116 mph	
* Wind Speed Specifications from	
ANGI/NIA AMM ED 1001 07	

| ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -