

## **Independence Series**

IRW - Internal with Winch Wire Halyard Ground Set Installation

## Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly

Alloy 6063-T6 Tapered Aluminum Tube

**E** Wall Thickness

Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle

## **D** Butt Diameter

meter IRW-GS

**Aluminum Collar** (Options Available) See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRW35C62G-T0Y-O2N-C0W-FSA

9

4

**B** Depth

Set

...9

2

## **IRW35C62**



**TRK-9660** 

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



IRW - WINCH
Reinforced Welded
Door Frame

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 6"	
E. Wall Thickness: .156"	
F. Top Diameter: 3.5"	
Flagpole Sections: 2	
Shaft Weight: 172 lbs.	
Hardware Weight: 23 lbs.	
Ground Sleeve Weight: 39 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 87 mph	
* Max Wind Speed No Flag: 116 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP\_010819\_1pg -1-