

Independence Series

IRW - Internal with Winch Wire Halyard

Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **IRW-GS D** Butt Diameter 9 Aluminum Collar (Options Available) 4 See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve .9 dimensions should be 3/16" Steel Support Plate determined by a qualified 12" Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

IRW35D72G-T0Y-O2P-C1G-FSA

IRW35D72



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0812-GLD-ES **HD Gold Anodized**

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 7"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 2	
Shaft Weight: 225 lbs.	
Hardware Weight: 30 lbs.	
Ground Sleeve Weight: 39 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 127 mph	
* Max Wind Speed No Flag: 187 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -