

Independence Series

IRW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box

Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length IRW-GS-1012 Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter 6 Aluminum Collar (Options Available) 4 See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set I Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site soil conditions. Lightning Spike -3/4" Diameter Steel Rod

Qty: 1
Location:

IRW50D13G-TAZ-O0F-C2C-FSA

IRW50D13



TRK-9800-58Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD HD Gold Anodized Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH Reinforced Welded Door Frame

Specifications
A. Mounting Height: 50'
B. Set Depth: 5'-0"
C. Total Length: 55'-0"
D. Butt Diameter: 10"
E. Wall Thickness: .188"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 422 lbs.
Hardware Weight: 52 lbs.
Ground Sleeve Weight: 83 lbs.
* Max Flag Size: 10' x 15'
* Max Wind Speed w/Nylon Flag: 118 mph
* Max Wind Speed No Flag: 164 mph
* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg -1-