

Independence Series

IRW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length IRW-GS-1012 Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter 6 Aluminum Collar (Options Available) 4 See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

Lightning Spike -3/4" Diameter Steel Rod

3/16" Steel Plate Welded to Sleeve

IRW50F13G-TAZ-O0F-C2C-FSA

B Depth

Set I

IRW50F13



TRK-9800-58Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD HD Gold Anodized Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 50'	
B. Set Depth: 5'-0"	
C. Total Length: 55'-0"	
D. Butt Diameter: 10"	
E. Wall Thickness: .250"	
F. Top Diameter: 4"	
Flagpole Sections: 3	
Shaft Weight: 536 lbs.	
Hardware Weight: 52 lbs.	
Ground Sleeve Weight: 83 lbs.	
* Max Flag Size: 10' x 15'	
* Max Wind Speed w/Nylon Flag: 140 mph	
* Max Wind Speed No Flag: 191 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP 010819 1pg -1-

Note: Foundation design not included. Foundation

dimensions should be

determined by a qualified Engineer familiar with site soil conditions.