

## **Independence Series**

IRW - Internal with Winch Wire Halyard Ground Set Installation

## **F** Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length IRW-GS-1012 Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter 6 Aluminum Collar (Options Available) 4 See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set I Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site soil conditions.

Lightning Spike -3/4" Diameter Steel Rod

IRW60D13G-TAZ-O0F-C2C-FSA

## **IRW60D13**



TRK-9800-58 Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD **HD Gold Anodized** Aluminum Ball



**COL1-A10S** FC-11 Spun Alum 1-Piece



SAT Satin Finish



**IRW - WINCH** Reinforced Welded Door Frame

Charifications
Specifications
A. Mounting Height: 60'
B. Set Depth: 6'-0"
C. Total Length: 66'-0"
D. Butt Diameter: 10"
E. Wall Thickness: .188"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 501 lbs.
Hardware Weight: 52 lbs.
Ground Sleeve Weight: 90 lbs.
* Max Flag Size: 12' x 18'
* Max Wind Speed w/Nylon Flag: 86 mph
* Max Wind Speed No Flag: 118 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg - 1 -