

Independence Series

IRW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length IRW-GS-1012 Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter 6 Aluminum Collar (Options Available) 4 See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) **B** Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set I Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Lightning Spike -3/4" Diameter Steel Rod

IRW70H23G-TAZ-O0G-C2N-FSA

IRW70H23



TRK-9800-58Int. Revolving Truck Sealed Bearings



SAT

BAL-1258-GLD HD Gold Anodized Aluminum Ball



COL1-A12S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IRW - WINCH Reinforced Welded Door Frame

Specifications	
A. Mounting Height: 70'	
B. Set Depth: 7'-0"	
C. Total Length: 77'-0"	
D. Butt Diameter: 12"	
E. Wall Thickness: .375"	
F. Top Diameter: 4"	
Flagpole Sections: 3	
Shaft Weight: 829 lbs.	
Hardware Weight: 53 lbs.	
Ground Sleeve Weight: 104 lbs.	
* Max Flag Size: 12' x 18'	
* Max Wind Speed w/Nylon Flag: 139 mph	
* Max Wind Speed No Flag: 181 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg -1-

Engineer familiar with site soil conditions.