

## **Sentry Series**

ISC - Internal Cam Cleat Rope Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope A Mounting Height Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Keyed Lock, Reinforced Door Frame, and Manually Operated Cam Cleat **ISC-GS D** Butt Diameter ٩. 4 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation dimensions should be 3/16" Steel Plate Welded to Sleeve .9 determined by a qualified 3/16" Steel Support Plate Engineer familiar with site 2 Lightning Spike soil conditions.

NOMINAL EXPOSED HEIGHT: Total Shaft Length of 25' flagpoles is 26'-6" with a Set Depth of 2'-6". With the Truck and Ornament attached, the nominal Mounting Height is 25'.

3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ISC25B51G-T0Y-O2M-C0L-FSA

## ISC25B51



**TRK-9660** 

Int. Revolving Truck Sealed Bearings




SAT

BAL-0512-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



**ISC - CAM CLEAT** Reinforced Raised Door Frame

0	
Specifications	
A. Mounting Height: 24'	
B. Set Depth: 2'-6"	
C. Total Length: 26'-6"	
D. Butt Diameter: 5"	
E. Wall Thickness: .125"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 93 lbs.	
Hardware Weight: 17 lbs.	
Ground Sleeve Weight: 26 lbs.	
* Max Flag Size: 5' x 8'	
* Max Wind Speed w/Nylon Flag: 98 mph	
* Max Wind Speed No Flag: 136 mph	
* Wind Speed Specifications from	
ΔΝSI/ΝΔΔΜΜ ΕΡ 1001-07	

| ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg - 1 -