

Sentry Series

ISC - Internal Cam Cleat Rope Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope A Mounting Height Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length

ISC-GS D Butt Diameter Aluminum Collar (Options Available) See Specification Box

Raised Access Door with Keyed Lock, Reinforced Door Frame, and Manually

Operated Cam Cleat

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer)

Perimeter caulked by Installer

3/16" Steel Plate Welded to Sleeve

3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod

Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ISC35D72G-T0Y-O2P-C1G-FSA

-6 4

Set Depth

ISC35D72



TRK-9660

Int. Revolving Truck Sealed Bearings




SAT

BAL-0812-GLD-ES **HD Gold Anodized**

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ISC - CAM CLEAT Reinforced Raised Door Frame

0 15 11	
Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 7"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 2	
Shaft Weight: 216 lbs.	
Hardware Weight: 18 lbs.	
Ground Sleeve Weight: 39 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 127 mph	
* Max Wind Speed No Flag: 187 mph	
* Wind Speed Specifications from	
A NIOL/NIA A NANA ED 4004 07	

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -