

## **Sovereignty Series**

ISW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be -6 determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike -

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

3/4" Diameter Steel Rod

soil conditions.

ISW20D51G-T0Y-O2M-C0L-FSA

## **ISW20D51**



**TRK-9660** 


Int. Revolving Truck Sealed Bearings



SAT

BAL-0512-GLD-ES **HD Gold Anodized** 

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



**ISW - WINCH** Reinforced Raised Door Frame

0 '6 '	
Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .188"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 103 lbs.	
Hardware Weight: 20 lbs.	
Ground Sleeve Weight: 23 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 182 mph	
* Max Wind Speed No Flag: 287 mph	
* Wind Speed Specifications from	
ANCUMA AMM ED 1001 07	

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg