

## **Sovereignty Series**

ISW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle

## ISW-GS Aluminum Collar (Options Available)

See Specification Box Perimeter caulked by Installer

**D** Butt Diameter

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve

3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod

**Note:** Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		

ISW20D61G-T0Y-O2N-C0W-FSA

...9

**B** Depth

Set

-6

12

## **ISW20D61**



**TRK-9660** 

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES

**HD Gold Anodized** Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



**ISW - WINCH** Reinforced Raised Door Frame

Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 6"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 122 lbs.	
Hardware Weight: 20 lbs.	
Ground Sleeve Weight: 28 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 229 mph	
* Max Wind Speed No Flag: 328 mph	
* Wind Speed Specifications from	

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg - 1 -