

Sovereignty Series

ISW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS 9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be ... determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

NOMINAL EXPOSED HEIGHT: Total Shaft Length of 25' flagpoles is 26'-6" with a Set Depth of 2'-6". With the Truck and Ornament attached, the nominal Mounting Height is 25'.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ISW25D61G-T0Y-O2N-C0W-FSA

ISW25D61



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ISW - WINCH
Reinforced Raised
Door Frame

Specifications
A. Mounting Height: 24'
B. Set Depth: 2'-6"
C. Total Length: 26'-6"
D. Butt Diameter: 6"
E. Wall Thickness: .188"
F. Top Diameter: 3.5"
Flagpole Sections: 1
Shaft Weight: 145 lbs.
Hardware Weight: 20 lbs.
Ground Sleeve Weight: 32 lbs.
* Max Flag Size: 5' x 8'
* Max Wind Speed w/Nylon Flag: 168 mph
* Max Wind Speed No Flag: 253 mph
* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg