

Sovereignty Series

ISW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be ... determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

3/4" Diameter Steel Rod

ISW30C51G-T0Y-O2M-C0L-FSA

CAFP_010819_1pg

ISW30C51



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0512-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ISW - WINCH Reinforced Raised Door Frame

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .156"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 127 lbs.	
Hardware Weight: 22 lbs.	
Ground Sleeve Weight: 32 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 86 mph	
* Max Wind Speed No Flag: 112 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

- 1 -

'OY-O2M-COL-FSA