

## **Sovereignty Series**

ISW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be ... determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions.

Customer Name:		
Dealer:		Qty: 1
Project:	Location:	
Notes:		

3/4" Diameter Steel Rod

ISW30D52G-T0Y-O2M-C0L-FSA

## **ISW30D52**



TRK-9660

Int. Revolving Truck Sealed Bearings




SAT

BAL-0512-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



ISW - WINCH
Reinforced Raised
Door Frame

Specifications		
A. Mounting Height: 30'		
B. Set Depth: 3'-0"		
C. Total Length: 33'-0"		
D. Butt Diameter: 5"		
E. Wall Thickness: .188"		
F. Top Diameter: 3"		
Flagpole Sections: 2		
Shaft Weight: 150 lbs.		
Hardware Weight: 22 lbs.		
Ground Sleeve Weight: 32 lbs.		
* Max Flag Size: 6' x 10'		
* Max Wind Speed w/Nylon Flag: 94 mph		
* Max Wind Speed No Flag: 131 mph		
* Wind Speed Specifications from		
ANCUMA AMM ED 1001 07		

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg