

Sovereignty Series

ISW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS

Aluminum Collar (Options Available)

See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve

3/16" Steel Support Plate Lightning Spike -3/4" Diameter Steel Rod Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

ISW35C51G-T0Y-O2M-C0L-FSA

...9

B Depth

Set

-6

12

ISW35C51



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0512-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ISW - WINCH
Reinforced Raised
Door Frame

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 5"	
E. Wall Thickness: .156"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 146 lbs.	
Hardware Weight: 23 lbs.	
Ground Sleeve Weight: 33 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 73 mph	
* Max Wind Speed No Flag: 87 mph	
* Wind Speed Specifications from	
ANGI/NAAMM ED 1001 07	

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg -1-