

## **Sovereignty Series**

ISW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be -6 determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

| Customer Name: |           |
|----------------|-----------|
| Dealer:        | Qty: 1    |
| Project:       | Location: |
| Notes:         |           |
|                |           |
|                |           |
|                |           |
|                |           |
|                |           |

ISW35C52G-T0Y-O2M-C0L-FSA

## ISW35C52



**TRK-9660** 

Int. Revolving Truck Sealed Bearings




SAT

BAL-0512-GLD-ES **HD Gold Anodized** 

Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



**ISW - WINCH** Reinforced Raised Door Frame

| Specifications                        |  |
|---------------------------------------|--|
| A. Mounting Height: 35'               |  |
| B. Set Depth: 3'-6"                   |  |
| C. Total Length: 38'-6"               |  |
| D. Butt Diameter: 5"                  |  |
| E. Wall Thickness: .156"              |  |
| F. Top Diameter: 3"                   |  |
| Flagpole Sections: 2                  |  |
| Shaft Weight: 151 lbs.                |  |
| Hardware Weight: 23 lbs.              |  |
| Ground Sleeve Weight: 33 lbs.         |  |
| * Max Flag Size: 6' x 10'             |  |
| * Max Wind Speed w/Nylon Flag: 73 mph |  |
| * Max Wind Speed No Flag: 87 mph      |  |
|                                       |  |
| * Wind Speed Specifications from      |  |
| ANGUNIA AMM ED 1001 07                |  |

| ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg