

Sovereignty Series

ISW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer)

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

ISW35C61G-T0Y-O2N-C0W-FSA

Set

...

12

ISW35C61



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0612-GLD-ES **HD Gold Anodized**

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ISW - WINCH Reinforced Raised Door Frame

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 6"	
E. Wall Thickness: .156"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 170 lbs.	
Hardware Weight: 23 lbs.	
Ground Sleeve Weight: 36 lbs.	
* Max Flag Size: 6' x 10'	
* Max Wind Speed w/Nylon Flag: 87 mph	
* Max Wind Speed No Flag: 116 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -

Note: Foundation design not included. Foundation

determined by a qualified

Engineer familiar with site

dimensions should be

soil conditions.