

## **Sovereignty Series**

ISW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be -6 determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Qty: 1
Location:

ISW35D71G-T0Y-O2P-C1G-FSA

## **ISW35D71**



**TRK-9660** 

Int. Revolving Truck Sealed Bearings



SAT

BAL-0812-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



Reinforced Raised
Door Frame

Specifications
A. Mounting Height: 35'
B. Set Depth: 3'-6"
C. Total Length: 38'-6"
D. Butt Diameter: 7"
E. Wall Thickness: .188"
F. Top Diameter: 3.5"
Flagpole Sections: 1
Shaft Weight: 216 lbs.
Hardware Weight: 30 lbs.
Ground Sleeve Weight: 39 lbs.
* Max Flag Size: 6' x 10'
* Max Wind Speed w/Nylon Flag: 127 mph
* Max Wind Speed No Flag: 187 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg -1-