

Sovereignty Series

ISW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Raised Access Door with Two (2) Mounting Bolts, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter ISW-GS ...9 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be -6 determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

| Qty: 1 |
|-----------|
| Location: |
| |
| |
| |
| |
| |
| |

ISW40C71G-T0Y-O2P-C1G-FSA

ISW40C71



TRK-9660

Int. Revolving Truck Sealed Bearings



SAT

BAL-0812-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



SAT Satin Finish



Reinforced Raised
Door Frame

| Specifications |
|---------------------------------------|
| A. Mounting Height: 40' |
| B. Set Depth: 4'-0" |
| C. Total Length: 44'-0" |
| D. Butt Diameter: 7" |
| E. Wall Thickness: .156" |
| F. Top Diameter: 3.5" |
| Flagpole Sections: 1 |
| Shaft Weight: 229 lbs. |
| Hardware Weight: 32 lbs. |
| Ground Sleeve Weight: 44 lbs. |
| * Max Flag Size: 8' x 12' |
| * Max Wind Speed w/Nylon Flag: 87 mph |
| * Max Wind Speed No Flag: 122 mph |
| |
| * Wind Speed Specifications from |
| ANSI/NAAMM FP 1001-07 |

CAFP_010819_1pg -1-