

Titan Series

IWW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter IWW-GS 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer

Qty: 1
Location:

2" Cap - Cement or Waterproof Compound

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

and Hardwood Wedges (By Installer)

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

IWW35D82G-TBL-O2P-C1S-FSA

B Depth

Set

IWW35D82



TRK-9800

Int. Revolving Truck Sealed Bearings




SAT

BAL-0812-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A08S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications
A. Mounting Height: 35'
B. Set Depth: 3'-6"
C. Total Length: 38'-6"
D. Butt Diameter: 8"
E. Wall Thickness: .188"
F. Top Diameter: 3.5"
Flagpole Sections: 2
Shaft Weight: 237 lbs.
Hardware Weight: 30 lbs.
Ground Sleeve Weight: 39 lbs.
* Max Flag Size: 6' x 10'
* Max Wind Speed w/Nylon Flag: 119 mph
* Max Wind Speed No Flag: 179 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

CAFP_010819_1pg -1-

Note: Foundation design not included. Foundation

determined by a qualified Engineer familiar with site

dimensions should be

soil conditions.