

## **Titan Series**

IWW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter IWW-GS 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Lightning Spike -

3/4" Diameter Steel Rod

IWW40C71G-T0Y-O2P-C1G-FSA

## **IWW40C71**





**TRK-9660** 

Int. Revolving Truck Sealed Bearings



BAL-0812-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



IWW - WINCH Flush Mount Hinged Door

Engineer familiar with site

soil conditions.

Specifications	
A. Mounting Height: 40'	
B. Set Depth: 4'-0"	
C. Total Length: 44'-0"	
D. Butt Diameter: 7"	
E. Wall Thickness: .156"	
F. Top Diameter: 3.5"	
Flagpole Sections: 1	
Shaft Weight: 230 lbs.	
Hardware Weight: 32 lbs.	
Ground Sleeve Weight: 44 lbs.	
* Max Flag Size: 8' x 12'	
* Max Wind Speed w/Nylon Flag: 65 mph	
* Max Wind Speed No Flag: 80 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	