

Titan Series

IWW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) A Mounting Height Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube IWW-GS-1012 Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter -6 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

3/16" Steel Plate Welded to Sleeve

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

IWW40D12G-TAZ-O0F-C2C-FSA

IWW40D12



TRK-9800-58 Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD **HD Gold Anodized** Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications	
A. Mounting Height: 40'	
B. Set Depth: 4'-0"	
C. Total Length: 44'-0"	
D. Butt Diameter: 10"	
E. Wall Thickness: .188"	
F. Top Diameter: 4"	
Flagpole Sections: 2	
Shaft Weight: 338 lbs.	
Hardware Weight: 32 lbs.	
Ground Sleeve Weight: 63 lbs.	
* Max Flag Size: 8' x 12'	
* Max Wind Speed w/Nylon Flag: 141 mph	
* Max Wind Speed No Flag: 204 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -

dimensions should be

soil conditions.

determined by a qualified Engineer familiar with site