

Titan Series

IWW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter IWW-GS 4' - 6" Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

and Hardwood Wedges (By Installer)

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

IWW40D81G-TBL-O2P-C1S-FSA

B Depth

Set

IWW40D81





TRK-9800

Int. Revolving Truck Sealed Bearings



BAL-0812-GLD-ES HD Gold Anodized

Aluminum Ball



COL1-A08S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications	
A. Mounting Height: 40'	
B. Set Depth: 4'-0"	
C. Total Length: 44'-0"	
D. Butt Diameter: 8"	
E. Wall Thickness: .188"	
F. Top Diameter: 4"	
Flagpole Sections: 1	
Shaft Weight: 260 lbs.	
Hardware Weight: 32 lbs.	
Ground Sleeve Weight: 55 lbs.	
* Max Flag Size: 8' x 12'	
* Max Wind Speed w/Nylon Flag: 91 mph	
* Max Wind Speed No Flag: 134 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg -1-

Note: Foundation design not included. Foundation

determined by a qualified Engineer familiar with site

dimensions should be

soil conditions.