

## **Titan Series**

IWW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) A Mounting Height Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube IWW-GS-1012 Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter - 6 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site Lightning Spike soil conditions.

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		

3/4" Diameter Steel Rod

IWW50F13G-TAZ-O0F-C2C-FSA

## **IWW50F13**



**TRK-9800-58**Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD HD Gold Anodized Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications		
A. Mounting Height: 50'		
B. Set Depth: 5'-0"		
C. Total Length: 55'-0"		
D. Butt Diameter: 10"		
E. Wall Thickness: .250"		
F. Top Diameter: 4"		
Flagpole Sections: 3		
Shaft Weight: 536 lbs.		
Hardware Weight: 52 lbs.		
Ground Sleeve Weight: 83 lbs.		
* Max Flag Size: 10' x 15'		
* Max Wind Speed w/Nylon Flag: 115 mph		
* Max Wind Speed No Flag: 165 mph		
* Wind Speed Specifications from		

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg -1-