

Titan Series

IWW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) A Mounting Height Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube IWW-GS-1012 Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter - 6 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

IWW60F13G-TAZ-O0F-C2C-FSA

IWW60F13




TRK-9800-58Int. Revolving Truck Sealed Bearings



SAT

BAL-1058-GLD HD Gold Anodized Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications
A. Mounting Height: 60'
B. Set Depth: 6'-0"
C. Total Length: 66'-0"
D. Butt Diameter: 10"
E. Wall Thickness: .250"
F. Top Diameter: 4"
Flagpole Sections: 3
Shaft Weight: 644 lbs.
Hardware Weight: 52 lbs.
Ground Sleeve Weight: 90 lbs.
* Max Flag Size: 12' x 18'
* Max Wind Speed w/Nylon Flag: 82 mph
* Max Wind Speed No Flag: 113 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

CAFP_010819_1pg -1-