

Titan Series

IWW - Internal with Winch Wire Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) A Mounting Height Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube IWW-GS-1012 Flush Access Door with Keyed Lock, Continuous Piano Hinge, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle **D** Butt Diameter -6 Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Set Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be 3/16" Steel Support Plate determined by a qualified Engineer familiar with site Lightning Spike -

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

3/4" Diameter Steel Rod

IWW60F23G-TAZ-O0G-C2N-FSA

IWW60F23



TRK-9800-58 Int. Revolving Truck Sealed Bearings



SAT

BAL-1258-GLD HD Gold Anodized Aluminum Ball



COL1-A12S FC-11 Spun Alum 1-Piece



SAT Satin Finish



IWW - WINCH Flush Mount Hinged Door

Specifications	
A. Mounting Height: 60'	
B. Set Depth: 6'-0"	
C. Total Length: 66'-0"	
D. Butt Diameter: 12"	
E. Wall Thickness: .250"	
F. Top Diameter: 4"	
Flagpole Sections: 3	
Shaft Weight: 667 lbs.	
Hardware Weight: 52 lbs.	
Ground Sleeve Weight: 90 lbs.	
* Max Flag Size: 12' x 18'	
* Max Wind Speed w/Nylon Flag: 117 mph	
* Max Wind Speed No Flag: 166 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -

soil conditions.