

F Top Diameter

Mounting Height

C Total Length

B Depth

Set

6"

2

Xtreme Series

XESR - Xtreme External Single Revolving Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

Halyard, Heavy-Duty #12 (3/8" Diameter)

Two (2) Heavy-Duty Stainless Steel

Two (2) Neoprene Flagsnap Covers

Alloy 6063-T6 Tapered Aluminum Tube

Cleat (Security Options Available)

Aluminum Collar (Options Available)

2" Cap - Cement or Waterproof Compound

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

and Hardwood Wedges (By Installer)

XESR-GS

Note: Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified Engineer familiar with site

See Specification Box

Braided Polyester Rope

Swivel Flagsnaps and

E Wall Thickness

See Specification Box

D Butt Diameter

See Specification Box

Perimeter caulked by Installer

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

evolving XESR30D72

- SAT



TRK-9420SS

HD Rev. Sealed Truck SS Spindle



ES
HD Gold Anodized

Aluminum Ball



CLA-9090-SAT | 7.5' from bottom Cleat Only



COL1-A07C

FC-11 Cast Alum 1-Piece

SAT Satin Finish



Qty: 1
Location:

Specifications

A. Mounting Height: 30'

B. Set Depth: 3'-0"

C. Total Length: 33'-0"

D. Butt Diameter: 7"

E. Wall Thickness: .188"

F. Top Diameter: 3.5"

Flagpole Sections: 2

Shaft Weight: 198 lbs.

Hardware Weight: 25 lbs.

Ground Sleeve Weight: 36 lbs.

* Max Flag Size: 6' x 10'

* Max Wind Speed w/Nylon Flag: 157 mph

* Max Wind Speed No Flag: 235 mph

* Wind Speed Specifications from

* Wind Speed Specifications from ANSI/NAAMM FP 1001-07

CAFP_010819_1pg

- 1 -

CAFP_010819_1pg - 2 -