

F Top Diameter

**Mounting Height** 

C Total Length

**B** Depth

Set

6"

7

## **Xtreme Series**

XESR - Xtreme External Single Revolving Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

Halyard, Heavy-Duty #12 (3/8" Diameter)

Two (2) Heavy-Duty Stainless Steel

Two (2) Neoprene Flagsnap Covers

Alloy 6063-T6 Tapered Aluminum Tube

Cleat (Security Options Available)

Aluminum Collar (Options Available)

2" Cap - Cement or Waterproof Compound

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

and Hardwood Wedges (By Installer)

**XESR-GS** 

**Note:** Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified Engineer familiar with site

See Specification Box

Braided Polyester Rope

Swivel Flagsnaps and

E Wall Thickness

See Specification Box

**D** Butt Diameter

See Specification Box

Perimeter caulked by Installer

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

## **XESR30F61**





**TRK-9420SS** 

HD Rev. Sealed Truck SS Spindle



**HD Gold Anodized** 

Aluminum Ball



CLA-9090-SAT | 7.5' from bottom Cleat Only



COL1-A06C

FC-11 Cast Alum 1-Piece



SAT Satin Finish



Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Matan	<u> </u>	

Notes:

**Specifications** A. Mounting Height: 30' B. Set Depth: 3'-0" C. Total Length: 33'-0" D. Butt Diameter: 6" E. Wall Thickness: .250" F. Top Diameter: 3.5" Flagpole Sections: 1 Shaft Weight: 197 lbs. Hardware Weight: 25 lbs. Ground Sleeve Weight: 36 lbs. \* Max Flag Size: 6' x 10' \* Max Wind Speed w/Nylon Flag: 150 mph \* Max Wind Speed No Flag: 229 mph \* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg

CAFP\_010819\_1pg - 2 -