

Xtreme Series

Rope Halyard Ground Set Installation

XESR - Xtreme External Single Revolving

Truck and Ornament (Options Available) F Top Diameter See Specification Box Halyard, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **XESR-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound **B** Depth and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Set Tamped Dry Sand (By Installer) **Note:** Foundation design not included. Foundation dimensions should be 3/16" Steel Plate Welded to Sleeve 6" determined by a qualified 3/16" Steel Support Plate 12 Engineer familiar with site Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		

XESR30F62



TRK-9420SS

HD Rev. Sealed Truck SS Spindle



CLA-9090-SAT | 7.5' from bottom Cleat Only



SAT

BAL-0612-GLD-**HD Gold Anodized**

Aluminum Ball



FC-11 Cast Alum 1-Piece



SAT Satin Finish

Specifications		
A. Mounting Height: 30'		
B. Set Depth: 3'-0"		
C. Total Length: 33'-0"		
D. Butt Diameter: 6"		
E. Wall Thickness: .250"		
F. Top Diameter: 3.5"		
Flagpole Sections: 2		
Shaft Weight: 202 lbs.		
Hardware Weight: 25 lbs.		
Ground Sleeve Weight: 36 lbs.		
* Max Flag Size: 6' x 10'		
* Max Wind Speed w/Nylon Flag: 150 mph		
* Max Wind Speed No Flag: 229 mph		
* Wind Speed Specifications from		
ANSI/NAAMM FP 1001-07		

CAFP_010819_1pg

CAFP_010819_1pg -2 -