

F Top Diameter

Mounting Height

C Total Length

Xtreme Series

XESR - Xtreme External Single Revolving Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

Halyard, Heavy-Duty #12 (3/8" Diameter)

Two (2) Heavy-Duty Stainless Steel

Two (2) Neoprene Flagsnap Covers

Alloy 6063-T6 Tapered Aluminum Tube

Cleat (Security Options Available)

Aluminum Collar (Options Available)

2" Cap - Cement or Waterproof Compound

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

and Hardwood Wedges (By Installer)

XESR-GS

Note: Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified Engineer familiar with site

See Specification Box

Braided Polyester Rope

Swivel Flagsnaps and

E Wall Thickness

See Specification Box

D Butt Diameter

See Specification Box

Perimeter caulked by Installer

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

XESR35F82

SAT



TRK-9420SS

HD Rev. Sealed Truck SS Spindle



HD Gold Anodized

Aluminum Ball



CLA-9090-SAT | 8' from bottom Cleat Only



COL1-A08C

FC-11 Cast Alum 1-Piece

SAT Satin Finish



Customer Name:	
Dealer:	Qty: 1

Project: Location: Notes:

Specifications A. Mounting Height: 35' B. Set Depth: 3'-6" C. Total Length: 38'-6" D. Butt Diameter: 8" E. Wall Thickness: .250" F. Top Diameter: 3.5" Flagpole Sections: 2 Shaft Weight: 287 lbs. Hardware Weight: 27 lbs. Ground Sleeve Weight: 50 lbs. * Max Flag Size: 6' x 10' * Max Wind Speed w/Nylon Flag: 181 mph * Max Wind Speed No Flag: 249 mph * Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

B Depth

Set

6"

7

CAFP_010819_1pg - 2 -