

F Top Diameter ~

## **Xtreme Series**

XESR - Xtreme External Single Revolving Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

See Specification Box

## XESR50F13

- SAT



TRK-9420SS-58 HD Rev. Sealed Truck SS Spindle



BAL-1058-GLD HD Gold Anodized Aluminum Ball



CLA-9090-SAT | 9.5' from bottom Cleat Only



FC-11 Cast Alum

1-Piece



SAT Satin Finish

		<b>-</b>	Halyard, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope
C Total Length	A Mounting Height	o~ <b>∢</b>	Two (2) Heavy-Duty 4-1/4" Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers
	А		<b>E Wall Thickness</b> Alloy 6063-T6 Tapered Aluminum Tube
C Total			Cleat (Security Options Available) See Specification Box
			XESR-GS-1012  D Butt Diameter
			Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer
		 FF	2" Cap - Cement or Waterproof Compound

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

and Hardwood Wedges (By Installer)

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Note: Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified

Engineer familiar with site

**Specifications** A. Mounting Height: 50' B. Set Depth: 5'-0" C. Total Length: 55'-0" D. Butt Diameter: 10" E. Wall Thickness: .250" F. Top Diameter: 4" Flagpole Sections: 3 Shaft Weight: 498 lbs. Hardware Weight: 28 lbs. Ground Sleeve Weight: 83 lbs. \* Max Flag Size: 10' x 15' \* Max Wind Speed w/Nylon Flag: 140 mph \* Max Wind Speed No Flag: 191 mph \* Wind Speed Specifications from ANSI/NAAMM FP 1001-07

XESR50F13G-TBA-O0F-SK-C2D-FSA CAFP\_010819\_1pg