

F Top Diameter -

ounting Height

Xtreme Series

XESR - Xtreme External Single Revolving Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

Halyard, Heavy-Duty #12 (3/8" Diameter)

Two (2) Heavy-Duty 4-1/4" Stainless Steel

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Note: Foundation design not included. Foundation

dimensions should be

soil conditions.

determined by a qualified

Engineer familiar with site

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

Two (2) Neoprene Flagsnap Covers

See Specification Box

Braided Polyester Rope

Swivel Flagsnaps and

XESR60H23

- SAT



TRK-9420SS-58 HD Rev. Sealed Truck SS Spindle



HD Gold Anodized

Aluminum Ball



CLA-9090-SAT | 10.5' from bottom Cleat Only



COL1-A12C

FC-11 Cast Alum 1-Piece



SAT Satin Finish

	ΑN		
C Total Length		<u> </u>	E Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube
C Tota			Cleat (Security Options Available) See Specification Box
			XESR-GS-1012
		/	D Butt Diameter
			Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer
	#		2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Specifications A. Mounting Height: 60' B. Set Depth: 6'-0" C. Total Length: 66'-0" D. Butt Diameter: 12" E. Wall Thickness: .375" F. Top Diameter: 4" Flagpole Sections: 3 Shaft Weight: 903 lbs. Hardware Weight: 28 lbs. Ground Sleeve Weight: 90 lbs. * Max Flag Size: 12' x 18' * Max Wind Speed w/Nylon Flag: 171 mph * Max Wind Speed No Flag: 228 mph * Wind Speed Specifications from ANSI/NAAMM FP 1001-07

XESR60H23G-TBA-O0G-SK-C2P-FSA CAFP_010819_1pg