

Estate Series

ESS - External Single Stationary Rope Halyard Ground Set Installation

F Top Diameter -Truck and Ornament (Options Available) See Specification Box Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Nickel Plated Cast Zinc Flagsnaps and Two (2) Neoprene Flagsnap Covers **E** Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **ESS-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or

NOMINAL EXPOSED HEIGHT: Total Shaft Length of 25' flagpoles is 26'-6" with a Set Depth of 2'-6". With the Truck and Ornament attached, the nominal Mounting Height is 25'.

Waterproof Compound

PVC Ground Sleeve

Tamped Dry Sand

(By Installer)

(By Installer)

Note: Foundation design not included. Foundation

determined by a qualified Engineer familiar with site

dimensions should be

soil conditions.

	U	J			
Customer Name:					
Dealer:				Qty: 1	
Project:			Loca	ition:	
Notes:					

ESS25C51






External Truck Single Stationary



CLA-9090-SAT | 7' from bottom Cleat Only



BAL-0512-GLD-ES HD Gold Anodized Aluminum Ball



FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications				
A. Mounting Height: 24'				
B. Set Depth: 2'-6"				
C. Total Length: 26'-6"				
D. Butt Diameter: 5"				
E. Wall Thickness: .156"				
F. Top Diameter: 3"				
Flagpole Sections: 1				
Shaft Weight: 87 lbs.				
Hardware Weight: 6 lbs.				
Ground Sleeve Weight: 5 lbs.				
* Max Flag Size: 5' x 8'				
* Max Wind Speed w/Nylon Flag: 111 mph				
* Max Wind Speed No Flag: 178 mph				
* Wind Speed Specifications from				
ANSI/NAAMM FP 1001-07				

Depth