

F Top Diameter -

Estate Series

ESS - External Single Stationary Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

See Specification Box

Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Nickel Plated Cast Zinc Flagsnaps and Two (2) Neoprene Flagsnap Covers **E** Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube **Cleat** (Security Options Available) See Specification Box **ESS-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or **Note:** Foundation design not included. Foundation Waterproof Compound Depth (By Installer) dimensions should be **PVC Ground Sleeve** determined by a qualified Engineer familiar with site Tamped Dry Sand soil conditions. (By Installer)

Customer Name:			
Dealer:		Qty: 1	
Project:	Loca	Location:	
Notes:			

ESS30C51

SAT



External Truck Single Stationary



CLA-9090-SAT | 7.5' from bottom Cleat Only



BAL-0512-GLD-**HD Gold Anodized** Aluminum Ball



FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications		
A. Mounting Height: 30'		
B. Set Depth: 3'-0"		
C. Total Length: 33'-0"		
D. Butt Diameter: 5"		
E. Wall Thickness: .156"		
F. Top Diameter: 3"		
Flagpole Sections: 1		
Shaft Weight: 109 lbs.		
Hardware Weight: 9 lbs.		
Ground Sleeve Weight: 6 lbs.		
* Max Flag Size: 6' x 10'		
* Max Wind Speed w/Nylon Flag: 86 mph		
* Max Wind Speed No Flag: 112 mph		
* Wind Speed Specifications from		
ANSI/NAAMM FP 1001-07		