

## **Xtreme Series**

XIRW - Xtreme Reinforced Int. w/ Winch Wire Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Heavy-Duty Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position). and Removable Winch Handle

## **D** Butt Diameter

Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate Lightning Spike -

3/4" Diameter Steel Rod

Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

XIRW-GS

NOMINAL EXPOSED HEIGHT: Total Shaft Length of 25' flagpoles is 26'-6" with a Set Depth of 2'-6". With the Truck and Ornament attached, the nominal Mounting Height is 25'.

|                | •         | 0 |  |        |  |
|----------------|-----------|---|--|--------|--|
| Customer Name: |           |   |  |        |  |
| Dealer:        |           |   |  | Qty: 1 |  |
| Project:       | Location: |   |  |        |  |
| Notes:         |           |   |  |        |  |
|                |           |   |  |        |  |
|                |           |   |  |        |  |
|                |           |   |  |        |  |
|                |           |   |  |        |  |

**XIRW25F61** 

SAT



**TRK-9660SS** 

Int. Rev. Sealed Truck SS Spindle



**BAL-0612-GLD-HD Gold Anodized** 

Aluminum Ball



COL1-A06C FC-11 Cast Alum 1-Piece



SAT Satin Finish



XIRW - WINCH Flush Mount Hinged Door

| Specifications                         |  |  |  |  |
|--|--|--|--|--|
| A. Mounting Height: 24'                |  |  |  |  |
| B. Set Depth: 2'-6"                    |  |  |  |  |
| C. Total Length: 26'-6"                |  |  |  |  |
| D. Butt Diameter: 6"                   |  |  |  |  |
| E. Wall Thickness: .250"               |  |  |  |  |
| F. Top Diameter: 3.5"                  |  |  |  |  |
| Flagpole Sections: 1                   |  |  |  |  |
| Shaft Weight: 184 lbs.                 |  |  |  |  |
| Hardware Weight: 35 lbs.               |  |  |  |  |
| Ground Sleeve Weight: 32 lbs.          |  |  |  |  |
| * Max Flag Size: 5' x 8'               |  |  |  |  |
| * Max Wind Speed w/Nylon Flag: 197 mph |  |  |  |  |
| * Max Wind Speed No Flag: 287 mph      |  |  |  |  |
|  |  |  |  |  |
| * Wind Speed Specifications from       |  |  |  |  |
| ANCI/NAAMMAED 1001 07                  |  |  |  |  |

ANSI/NAAMM FP 1001-07

XIRW25F61G-TBK-O2N-C0X-FSA CAFP\_010819\_1pg

- 6

**B** Depth

Set

2